

**MISSOURI PUBLIC SERVICE COMMISSION
MANUFACTURED HOUSING DEPARTMENT
APPROVAL OF ANCHORING SYSTEMS**

HOME PRIDE

800-759-5910

MODEL	MARK	DESCRIPTION	SOIL TYPE	DUAL STRAP
HP-3	HP-3	Double 4" Helix 3/4" x 30" w/HP32 Stab. Plate	475 in. lbs. & above	NO
HP-3	HP-3	Double 4" Helix 3/4" x 30" w/HP30 or HP31 Stab. Plate	2,3	NO
HP-4	HP-4	6" Helix 5/8" x 48"	2,3,4	NO
HP-5	HP-5	6" Helix 3/4" x 48"	275 in. lbs. & above	NO
HP-10	HP-10	36" Cross Drive Rock Anchor	Solid Rock Only	NO
HP-11	HP-11	48" Cross Drive Rock Anchor	Solid Rock Only	NO
HP-17	HP-17	Double 4"/ 6" Helix 3/4" x 36" w/HP32 Stab. Plate	300 in. lbs. & above	NO
HP-17	HP-17	Double 4"/ 6" Helix 3/4" x 36" w/HP30 or HP31 Stab. Plate	2,3	NO
HP-13	HP-13	J Hook Concrete Anchor	Concrete Only	
HP-14	HP-14	J Hook Concrete Anchor w/Swivel Head	Concrete Only	
HP-12	HP-12	Steel Expansion Concrete Anchor	Concrete Only	
HP-20	HP-20	Double-Slot Buckle Frame Tie		
HP-21	HP-21	Single-Slot Buckle Frame Tie		
HP-22	HP-22	Frame Tie w/Hook		
HP-30	HP-30	Stabilizer Plate		
HP-31	HP-31	Stabilizer Plate		
HP-32	HP-32	Stabilizer Plate		
	Home Pride, Inc.	Galvanized Steel Strapping		
	Home Pride, Inc.	AB Anchor Bolt		
	Home Pride, Inc.	Strap Splice Seal		

STANDARDS FOR INSTALLATION:

- 1) Anchors and all components must be installed per manufacturers instructions.
- 2) Anchors are approved for and can be used in designated soil type only.
- 3) One strap per anchor unless the anchor is approved for dual strap use.
- 4) Consult manufactured home set up instructions for number of frame tie downs, over the roof tie downs, and tie down spacing.
- 5) Soil Classifications, (1) Solid Rock, (2) 550+ inch lbs, (3) 350-449 inch lbs, (4) 200-349 inch lbs, under 200 unclassified.

DATE: May 5, 2006

Ron Pleus

Ron Pleus, Director
Manufactured Housing and Modular units Program

System used on your home _____