

**MISSOURI PUBLIC SERVICE COMMISSION
MANUFACTURED HOUSING PROGRAM
APPROVED ANCHOR PRODUCTS**

MINUTE-MAN ANCHORS, INC. 800-438-7277

MODEL	MARK	DESCRIPTION	TEST VALUE ANCHOR PROBE (inch lbs.)
650-DH 5/8" *	MMA-2	50" Double Head Auger Anchor	350 inch lbs. & above
650-DH 3/4" *	MMA-4	50" Double Head Auger Anchor	350 inch lbs. & above
636-DH 3/4" *	MMA-28	36" Double Head Auger Anchor	400 inch lbs. & above
860-DH 3/4" *	MMA-85	60" Long, 8" Disc Double Head Anchor	175 inch lb. & above
4430-DH 5/8" *	MMA-30	30" Double Head/Disc Auger Anchor	400 inch lbs. & above
4430-DH 3/4" *	MMA-6	30" Double Head/Disc Auger Anchor	400 inch lbs. & above
4430-DH 3/4" *	MMA-6	30" Double Head with NC 1 Stabilizer Cap	400 inch lb. & above
4430-EZDH 3/4" *	MMA-92	32" Double Head/Double Disc Auger Anchor / No Comp. Disc	525 inch lb. & above
4450-DH 3/4" *	MMA-55	50" Long (2) 4" Disc Double Head Anchor	300 inch lb. & above
4636-DH 3/4" *	MMA-52	36" Double Head/4" and 6" Helix	300 inch lb. & above
4636-EZDH 3/4" *	MMA-93	36" Double Head/4" and 6" helix	300 inch lb. & above
36-XDH *	MMA-35	36" Double Head Cross Drive Anchor	Solid Rock Only
48-XDH	MMA-8	48" Double Head Cross Drive Anchor	Solid Rock Only
GW 2 *	GW2-18	18" w/4" Helix/NC2 Stabilizer/Two 32" Rods	450 inch lb. & above
GW1	GW1	Rock Anchor w/NC2 Stabilizer/Two 16" Rods	Solid Rock Only
THDH *	MMA-18	Double Tension Head	Concrete
210-PDH *	MMA-14	Double Head Tension Device for Concrete	Concrete
210-JDH *	MMA-42	Swivel Double Head Anchor with Base	Concrete
	NC 1	Nu-Concept Stabilizer Cap	
	NC 2	Stabilizer Cap for GW series anchors	
	MMA-29	Frame Strap with Clamp	
	MMA-32	Frame Buckle with Strap	
MMA-33 Frame Clamp	MMA-33	Locking Frame Clamp II	
		Galvanized Steel Strapping	
	MMA	Strap Extending Seals	
MILL BOLT		Anchor Tension Bolt	
SLOT BOLT		Anchor Tension Bolt	
44-RB & 66-RB		Roof Brackets	
MMA-SD2A		Anchor Stabilizing Device	260 inch lbs. & above
MMA LLBS	SD3	Longitudinal & Lateral Bracing System	250 inch lbs. & above
MMALLBS	FT	LLBS Wet/Dry Concrete Application	Concrete

* These anchors are approved for vertical pull.

STANDARDS FOR INSTALLATION:

1. Anchors and all components must be installed per manufacturer's instructions.
2. Anchors are approved for designated soil per test value in inch pounds.
3. Consult manufactured home set up instructions for number of frame tie downs, over the roof tie downs, and tie down spacing.
4. Systems must be approved for use by the home manufacturer.

All single section homes require an approved anchor for the soil within two feet of each corner.

*MUST BE A LICENSED INSTALLER WITH THE PUBLIC SERVICE COMMISSION
TO ANCHOR NEW HUD HOMES PURSUANT TO 700.656*

Revision Date: September, 2013